

**Warning: Improper wiring of any electrical device can cause serious injury or death. These wiring devices should only be installed by a certified electrician or other qualified person.**

**Caution: This product should be installed in accordance with the National Electrical Code and all applicable local codes and standards.**

### **TURN OFF POWER BEFORE INSTALLING.**

1. Attach mounting lugs to box using provided screws.
2. Pull power supply wires into box, securing with appropriate fitting.
3. Mount box to wall using 1" long screws (not included) that are appropriate for your wall type.
4. Attach ground wire to box with green ground screw.
5. Wire and mount device(s) according to manufacturer's instructions.
6. Close any remaining holes with enclosed plugs and use a silicone sealing compound for wet location installation.
7. Mount cover to outlet box using gaskets as required to comply with wet location installation and per the cover manufacturer's instructions.

**Advertencia: El cableado incorrecto de cualquier dispositivo eléctrico puede causar lesiones graves o la muerte. Estos dispositivos de cableado solo deben ser instalados por un electricista certificado u otra persona calificada.**

**Precaución: Este producto debe instalarse de acuerdo con el Código Eléctrico Nacional y todos los códigos y normas locales aplicables.**

### **APAGUE LA ENERGÍA ANTES DE INSTALAR.**

1. Fije las agarraderas de montaje a la caja usando los tornillos proporcionadas.
2. Tire de los cables de la fuente de alimentación en la caja, asegurándola con un accesorio apropiado.
3. Monte la caja en la pared usando tornillos de 1 "de largo (no incluidos) que sean apropiados para su tipo de pared.
4. Fije el cable tierra a caja con un tornillo de tierra verde.
5. Cablee y monte los dispositivo (s) de acuerdo con las instrucciones del fabricante.
6. Cierre los orificios restantes con los tapones incluidos y utilice un compuesto de sellado de silicona para la instalación de ubicación húmeda.
7. Monte la tapa en la caja de salida utilizando las juntas necesarias para cumplir con la instalación en lugares húmedos y según las instrucciones del fabricante de la tapa.